



TVM 136 Draft Stop

Product Description:

TVM Draft Stop is a high quality caulk that cures to form a tight seal with the capability to withstand temperatures of up to 1383°F (749°C).

Colors and Packaging:

Size	10.1 fl.oz.	
Color	Red	
Part No. (US)	1-91-12-003 (US)	5-91-12-003 (CDN)

Features:

- Meets ASTM E-136 requirements
- Forms a heat and fire resistant shield
- Will not crack after curing

Compatible Surfaces:

- Bricks
- Metal
- Concrete

Applications:

- Sealing joints in high temperature areas
- Draft stopping in wood frame construction

Joint Dimension:

Minimum Width: 5 mm  
Maximum Width: 20 mm

Application Notes:

- Surfaces should be clean, free of dust and grease
- Moisten application surface for increased adhesion
- Do not use in temperatures below 32°F (0°C)

Shelf Life:

12 months in unopened packaging when stored in a cool, dry place between the temperatures of 40°F and 96°F (4°C and 36°C).

Health and Safety Recommendations:

- Apply standard industrial hygiene
  - In case of emergency, contact INFOTRAC at 1.800.535.5053
- Please consult product label and MSDS for additional health and safety information.*

Remarks:

Do not use in areas where the possibility of constant water immersion is present. Warming of the heating installation for 12 hours after application prevents bubble forming and improves structure.

Shipping Specifications:

Size	Units/ Case	Case Weight	Dimensions (L" × W" × H")		Cases/ Pallet	Pallet Weight
			Case	Pallet		
10.1 fl.oz.	12	16 lbs	8 × 6 × 13	48 × 40 × 52	144	2304 lbs

TDS -0191-07

